

22"

HIGH VELOCITY FAN



STANDARD YM - YOKE MOUNT

ADDITIONAL MOUNTING OPTIONS:



CW Column-Wall
82 lbs (w/ fan)



PS Portable Stroller
105 lbs (w/ fan)



PB Pedestal Base
81 lbs (w/ fan)

SHIPPING WEIGHT:

SIZE	CFM	HP	FAN DIMENSIONS			AIR THROW DISTANCE	SHIPPING WEIGHT
			W	D	ID		
22"	5570	1/2	29"	16"	22.5"	100'	69 lbs

FEATURES

Propeller: 21" Diameter, 3 Blade GalvAlum, 19°
Fan Inlet/Outlet: Galvanized 16 Gauge Spun Steel
Finger Guards: OSHA Compliant, Stainless Steel Spiral
Power Cord (115V Only): 12' Length
RPM: 1725
Decibels: 73.6 @ 20' - 81.2 @ 3'
Coverage: 3600 ft²

Warranty: 2 Years

MOTOR

VOLTAGE	MOTOR AMPS	RUNNING AMPS
115V/208-230V*	6.0/3.0-2.9	5.9/2.9-2.8
208-230/460V	2.4-2.3/1.2	2.3-2.2/1.1
277V	1.85	1.75


Enclosure: TEAO Standard, WD Available

Frame: 56

Ambient Temperature: 104°F

Duty Cycle: Continuous

*standard



Above velocities shown in feet/minute.

AIR FLOW PATTERN